

VS-XL70U

1024 x 768 pixels (XGA)

Display Wall Projection Engine

70 **Seventy Series:**



FEATURING



1: INTELLIGENCE:

- Advanced Smart Lamp System
- Advanced Color Space Control
- Digital Gradation Circuit

2: FLEXIBILITY:

- Custom System Configuration
- Easily Upgradable

3: INTERNAL PROCESSING:

- Capable of up to 6 windows per display (with no "desktop image")

4: AUTO-BALANCING:

- Dynamic Color and Brightness Balancing

5: EASY SETUP:

- Auto Geometry and Color Adjustment
- Front or rear maintenance available

6: DURABILITY:

- Color Wheel and Fan Wheel Built to Last Over 11 Years of 24/7 Use

7: REDUNDANCY

- Input Redundancy for Mission-Critical Applications





VS-XL70U

**1024 x 768 pixels (XGA)
Display Wall Projection Engine**

DLP® Display Cube Projection Engine

DISPLAY TECHNOLOGY	1-Chip DLP™ (0.7" DMD 1-Chip)
LIGHT OUTPUT	Bright: 860 ANSI Lumens; Normal: 760 ANSI Lumens
NATIVE RESOLUTION	1024 x 768 pixels (XGA)
SCREEN SIZE	50" - 67" diagonal viewable
CONTRAST RATIO	2200:1 (typical)
PIXEL CLOCK RATE	25 - 162 MHz
THROW DISTANCE	50": 744.1 +/- 22.3mm, 60": 900.1 +/- 27.0mm, 67": 1009.3 +/- 30.3mm
THROW RATIO	0.771:1 nominal
EXIT PUPIL-LENS TOP	39.9 mm
RGB INPUT SCANNING FREQUENCY	Horizontal: 31.5 - 92.0 kHz; Vertical: 49 - 85 Hz
SUPPORTED RESOLUTION SIGNALS	VGA (640x480) - WUXGA (1920x1200)
OPTIONAL INPUT CARDS (EACH DISPLAY REQUIRES 3 INPUT CARDS)	VC-B70G2 - INPUT CARD for Analog RGB Signals (5 BNC x 1 / D-Sub mini 15 pin x 1) VC-B70D2 - INPUT CARD for Digital Video Signals (DVI-D x 2) VC-B70V2 - INPUT CARD for Analog Video Signals (3 BNC x 2) VC-B70DC - INPUT CARD for Daisy Chain (D-Sub 15 x 1 / DVI-D x 1 / 3 BNC x 1) VC-B70SD1 - INPUT CARD for SDI Signals (2 BNC)
CONTROL SIGNAL INPUT/OUTPUT	RS-232C: D-Sub 9 pins x 2 (input, output) Mitsubishi original control link; Wired Remote: F3.5 Jack; IR Receiver, LAN Input, Rear LED Notification Screen, Front LED Indicator
LAMP TYPE	High pressure mercury lamp 132W/150W
AVERAGE LAMP LIFE	10,000 hours/6,000 hours
PRODUCT DIMENSIONS	28.3 x 15.3 x 13.6" (720 x 388 x 345 mm) (W x H x D in)
WEIGHT	29kg / 64lbs lbs.
LAMP CONFIGURATION	Single Lamp
ESTIMATED LAMP LIFE	10,000 hours (Normal mode) 6,000 hours (Bright mode)
POWER CONSUMPTION	230W @ 132W, 260W @ 150W
VOLTAGE RANGE	AC 100 – 240V +/-10% , 50/ 60Hz +/-1Hz
THERMAL DISSIPATION	223.6kcal/h (887BTU/h)
ENVIRONMENT	Condition at Operation: 50-95 F; (10-35 C), Condition at Storage: -4-122 F; (-20-50 C)
SAFETY APPROVAL	UL60950-1, CSAC22.2No.60950-1, EN60950-1AS60950-1, GB4943
EMC	FCC part15 Subpart B Class A, ICES-003 Issue No.4 Class A, EN55022 Class A, EN55024, EN61000-3-2, EN61000-3-3, K00022 Class A, K00024, AS/NZS CISPR 22 Class A, GB9254 Class A, GB17625.1

SPECIFICATIONS AND DATA SUBJECT TO CHANGE WITHOUT NOTICE



MITSUBISHI DIGITAL ELECTRONICS AMERICA, INC.
Presentation Products Division
Toll Free: 888.307.0349
Email: ppdinfo@mdea.com
www.mitsubishi-presentations.com

Canada
Mitsubishi Electric Sales Canada Inc.
Information Technologies Group
Phone: 905.475.7728
www.mitsubishielectric.ca